

Specificaiton

Overview

Input Connectors:	XLR x 2, RCA x 2
Tubes:	Genalex PX300B×2 (Output) TUNG-SOL 6SN7GTB×2 (Driver) RCA 22DE4×4 (Rectifier)
Dimensions	
Amplifier:	286mm×368mm×210mm
Power Supply:	150mm×345mm×210mm
Weight	
Amplifier:	19kg
Power Supply:	10kg
Fuse:	~220V-240V: T1.6AL250V; ~100V-120V: T3.15AL250V
Output Tube Fuse :	T100mA E250V
Power Consumption:	185W
Working Condition Temp:	0°C~40°C; Humidity: 20% - 80%
Storage Condition Temp:	-20°C~70°C; Humidity: 20% - 90%

Headphone output

Rated Output (per channel)	
4pin XLR (BAL)	2000mW (L); 2400mW (M); 6000mW (H)
4.4mm (BAL)	1400mW (L); 2200mW (M); 5400mW (H)
3.5mm (SE)	1200mW (L); 2200mW (M); 5000mW (H)
Frequency Range:	10Hz~45kHz ±3dB
TH+D:	1% (1kHz)
Sensitivity:	200mV~650mW
S/N Ratio:	100dB (A-Weighted)
Headphone Impedance:	L: 8~64Ω; M: 65~250Ω; L: 251~600Ω
Headphone Connectors:	4-pin XLR x1, 4.4mm x1, 6.35mm x1

Speaker Output

Rated Output:	8W+8W
Frequency Range:	10Hz~40kHz ±3dB
TH+D:	1% (1kHz)
S/N Ratio:	95dB (A-Weighted)
Input Sensitivity:	400mV
Output Impedance:	4~8Ω
Input Impedance:	50kΩ