

DALI GARDIAN
OW 6

DALI



ON-WALL OUTDOOR
HI-FI LOUDSPEAKER

[DALI-SPEAKERS.COM](https://www.dali-speakers.com)

DALI GARDIAN OW 6

|

SPECIFICATIONS

Frequency range	47 - 25,000 Hz +/- 3dB
Sensitivity	84 dB @ 1 m for 2.83 V
Nominal impedance	6 Ohm
Maximum SPL	103 dB
Crossover frequency	2,700 Hz
Crossover principle	2-way
Recommended amplifier power	50 - 200 Watt
High frequency driver(s)	1 x 25 mm soft dome (Co-axially mounted)
High frequency diaphragm	Soft woven fabric
Low/Mid frequency driver(s)	1 x 5 inch
Low/Mid frequency diaphragm	Polypropylene
Connection input(s)	Single wire
Enclosure type	Tuned Mass Enclosure, 2 x 5 inch (oval) passive radiators
Other features	Click n' Connect wall bracket
Installation location	On-Wall / On-Ceiling
Recommended placement	Ceiling / Front / Centre / Surround
IP rating	IP 67
Outer dimensions incl. grille (H x W x D)	200 x 372 x 206 mm 7.87 x 14.65 x 8.11 inches
Weight incl.grille	4.08 kg 9 lbs
Shipping weight (pair)	10.4 kg 22.92 lbs
Finish	White / Black
Included accessories	Wall Mounting Template
Optional accessories	Wall Bracket Cover

All technical specifications are subject to change without notice.

