



## SL-1500CEG-W HI-FI TURNTABLE SYSTEM

The highly acclaimed Technics SL-1500C turntable now available in white



The **SL-1500C-W** is a turntable system offering pure aesthetics combined with exceptional functionality and ease of use.

- ✓ **Direct drive motor** and sophisticated motor control technology for stable, high precision rotation
- ✓ **Highly sensitive universal S-shaped tonearm** with height adjustment mechanism and **automatic lifter function** to minimize unnecessary needle and disc wear.
- ✓ **Built-in Ortofon 2M RED cartridge** for easy installation and immediate vinyl playback
- ✓ **Built-in and switchable Phono PreAmp (MM)**
- ✓ **Forged aluminum platter** minimizes vibration and eliminates unwanted resonance
- ✓ **Two-layer chassis and insulated feet** for optimal vibration damping characteristics



# SL-1500CEG-W HIFI TURNTABLE SYSTEM

Code EAN : 5025232945818

**SPECIFICATIONS**

<b>Stable rotation technology</b>	Direct drive motor with single rotor and stators without ferrous core High precision motor control
<b>Anti-vibration construction</b>	Two-layer platter with excellent damping performance Construction of the rigid cabinet Insulated feet incorporating an absorbent silicone body
<b>High quality components</b>	High sensitivity tonearm Gold-plated connectors
<b>Technics Design</b>	Heavy aluminum platter
<b>Turntable</b>	
<b>Type</b>	Direct Drive Manual Turntable
<b>Motor</b>	Brushless DC Motor
<b>Turntable Speeds</b>	33 1/3, 45, 78 rpm
<b>Adjust Range</b>	-
<b>Starting Torque</b>	0.18 N · m / 1.8 kg · cm
<b>Build-up Characteristics</b>	0.7 s. from standstill to 33 1/3 rpm
<b>Wow and Flutter</b>	0.025% W.R.M.S.
<b>Signal-to-noise ratio</b>	78dB (IEC 98A)
<b>Turntable Platter</b>	Aluminum die-cast Diameter : 332mm Weight : Approx. 2.0kg (Including Turntable Sheet)
<b>Tonearm</b>	
<b>Type</b>	Universal Static Balance
<b>Effective Length (from the tonearm pivot to the stylus)</b>	230 mm
<b>Overhang</b>	15mm
<b>Tracking Error Angle</b>	Within 2° 32' (at the outer groove of 30cm(12") record) Within 0° 32' (at the inner groove of 30cm(12") record)

<b>Offset Angle</b>	22°
<b>Arm Height Adjustment Range</b>	0 - 6 mm
<b>Stylus Pressure Adjustment Range</b>	0 - 4g (Direct Reading)
<b>Headshell weight</b>	Approx. 7.6g
<b>Applicable Cartridge Weight Range(including Headshell)</b>	5.6 - 12.0g (Without auxiliary weight) 14.3 - 20.7g (including headshell) 10.0 - 16.4g (With auxiliary weight) 18.7 - 25.1g (Including headshell)
<b>Cartridge Mounting Dimension</b>	-
<b>Head Shell Terminal Lug</b>	1.2mmφ 4-pin terminal lug
<b>Bundled Cartridge</b>	Ortofon 2M Red
<b>Built-in Phono Equalizer</b>	
<b>Gain</b>	37dB
<b>RIAA deviation</b>	±1dB (20Hz - 20kHz)
<b>Terminals</b>	
<b>Audio Output</b>	PHONO (Pin Jack) x 1 EARTH TERMINAL x 1 LINE (Pin Jack) x 1
<b>General</b>	
<b>Power Supply</b>	AC110-240 V, 50 Hz / 60 Hz
<b>Power Consumption</b>	8 W Approx. 0.2W (Standby)
<b>Dimensions (W x H x D)</b>	453 x 173 x 372 mm
<b>Weight</b>	Approx. 9.9 kg
<b>Accessories</b>	Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Head shell, Cartridge(Ortofon 2M Red), PHONO cable, PHONO earth lead, AC power supply cord, Owner's Manual

