



SU-GX70EG-K AMPLIFIED NETWORK PLAYER

Technics' first amplified network player with video connectivity



- ✓ **JENO Engine and LANC** ensure highly pure sound free of jitter and noise for a truly audiophile sound.
- ✓ **Optimized power supplies for both digital and analog circuits** as well as for the amplifier section for low noise and less interference.
- ✓ **HDMI ARC (Audio Return Channel) input** with special treatment of the video signals for eliminating bad effects on the audio signal, reaching a highly pure sound.
- ✓ **Touch screen** for better ergonomics.
- ✓ **High-end amplifier with a low-noise Phono MM input** from Technics Grand Class grade.
- ✓ **A multitude of terminals** : Line input x2, Digital input x3, USB A/B, Pre-out input.
- ✓ **Rich connectivity**: Chromecast, AirPlay2, Wi-Fi, Bluetooth, Spotify, TIDAL, Qobuz, Deezer, Amazon HD, Roon Ready, Internet Radio.



SU-GX70EG-K AMPLIFIED NETWORK PLAYER

Code EAN : 5025232932948

TECHNICAL SPECIFICATIONS

Covers most digital audio media available today		
	Chromecast Built-In™	
	AirPlay2	
	Wi-Fi	
	Bluetooth	
	Spotify	
	TIDAL	
	Qobuz	
	Deezer	
	Amazon HD	
	Roon Ready (after OTA firmware update)	
	Internet Radio	
A very pure digital signal		
	JENO (Jitter Elimination and Noise-shaping Optimization) Engine	
	LAPC (Load Adaptive Phase Calibration)	
	Space Tune feature	
	Pure Amplification Mode	
Uncompromising sound quality thanks to high-quality Technics technologies		
	High Speed Silent Twin Power Supply	
	Low-noise Phono equalizer	
	Noise cancellation circuit	
Sound quality		
Output Power		40W+40W(1kHz,T.H.D.1.0%,8Ω,20kHz LPF) 80W+80W(1kHz,T.H.D.1.0%,4Ω,20kHz LPF)
Load Impedance		4Ω-16Ω
Frequency Response	PHONO (MM)	20Hz - 20kHz (RIAA DEVIATION ±1dB, 4Ω)
	LINE	20Hz - 40kHz (-3dB, 4Ω)
	DIGITAL	20Hz - 80kHz (-3dB, 4Ω)
Input Sensitivity / Input Impedance	PHONO (MM)	2.0 mV / 47 kΩ
	LINE	200 mV / 23 kΩ
Terminals		
Analogue Input Terminal		LINE x 2 PHONO (MM) x1
Digital Input Terminal		Optical digital x2 Coaxial digital x1 USB-A x1 USB-B x1
Analogue Output Terminal		PRE OUT x1
Digital Output Terminal		HDMI ARC
Headphone Output		Yes, Stereo Ø6.3 mm

USB-A	Standard	USB 2.0 High-speed USB Mass Storage class	
	iPod/iPhone/iPad	No	
	Support Codec	WAV	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		FLAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		DSD	Yes (2.8 MHz, 5.6 MHz, 11.2 MHz)
		AIFF	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		ALAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		AAC	Yes (32, 44.1, 48, 88.2, 96 kHz/16-320kbps)
MP3	Yes (32, 44.1, 48 kHz / 16-320 kbps)		
PC(USB-B)	Standard	USB 2.0 High-speed USB Audio Class 2.0, Asynchronous mode	
	Support Codec	LPCM DSD	
	DSD control mode	ASIO Native mode, DoP mode	
Connectivity			
MQA Decoder			
		Yes	
LAN (DMR)	Support Codec	WAV	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		FLAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		DSD	Yes (2.8 MHz, 5.6 MHz, 11.2 MHz)
		AIFF	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		ALAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		AAC	Yes (32, 44.1, 48, 88.2, 96 kHz/16-320kbps)
MP3	Yes (32, 44.1, 48 kHz / 16-320 kbps)		
Ethernet Interface			
		LAN (100 Base-TX / 10 Base-T)	
Wi-Fi			
		IEEE 802.11a/b/g/n/ac/ax 2.4 GHz band / 5 GHz band	
Chromecast Built-In™			
		Yes	
AirPlay 2			
		Yes	
Bluetooth® (Support codec)			
		Yes (AAC, SBC)	
Tuner			
		DAB/DAB+/FM	
General			
Power Supply		AC 220 V - 240 V, 50/60 Hz	
Power Consumption		63 W	
Dimensions (W x H x D)		430 x 98 x 368 mm	
Weight		Approx. 6.6 kg	
Color		Black	
Accessories		AC Cord, DAB Indoor Antenna, Remote Control, Batteries for Remote Control, Owner's Manual	





SU-GX70EG-S AMPLIFIED NETWORK PLAYER

Technics' first amplified network player with video connectivity



✓ **JENO Engine and LAPC** ensure highly pure sound free of jitter and noise for a truly audiophile sound.

✓ **Optimized power supplies for both digital and analog circuits** as well as for the amplifier section for low noise and less interference.

✓ **HDMI ARC (Audio Return Channel) input** with special treatment of the video signals for eliminating bad effects on the audio signal, reaching a highly pure sound.

✓ **Touch screen** for better ergonomics.

✓ **High-end amplifier with a low-noise Phono MM input** from Technics Grand Class grade.

✓ **A multitude of terminals** : Line input x2, Digital input x3, USB A/B, Pre-out input.

✓ **Rich connectivity**: Chromecast, AirPlay2, Wi-Fi, Bluetooth, Spotify, TIDAL, Qobuz, Deezer, Amazon HD, Roon Ready, Internet Radio.



SU-GX70EG-S AMPLIFIED NETWORK PLAYER

Code EAN : 5025232932955

TECHNICAL SPECIFICATIONS

Covers most digital audio media available today	Chromecast Built-In™	
	AirPlay2	
	Wi-Fi	
	Bluetooth	
	Spotify	
	TIDAL	
	Qobuz	
	Deezer	
	Amazon HD	
	Roon Ready (after OTA firmware update)	
Internet Radio		
A very pure digital signal	JENO (Jitter Elimination and Noise-shaping Optimization) Engine	
	LAPC (Load Adaptive Phase Calibration)	
	Space Tune feature	
Uncompromising sound quality thanks to high-quality Technics technologies	Pure Amplification Mode	
	High Speed Silent Twin Power Supply	
	Low-noise Phono equalizer	
Sound quality	Noise cancellation circuit	
	Output Power	
Output Power	40W+40W(1kHz,T.H.D.1.0%,8Ω,20kHz LPF) 80W+80W(1kHz,T.H.D.1.0%,4Ω,20kHz LPF)	
Load Impedance	4Ω-16Ω	
Frequency Response	PHONO (MM)	20Hz - 20kHz (RIAA DEVIATION ±1dB, 4Ω)
	LINE	20Hz - 40kHz (-3dB, 4Ω)
	DIGITAL	20Hz - 80kHz (-3dB, 4Ω)
Input Sensitivity / Input Impedance	PHONO (MM)	2.0 mV / 47 kΩ
	LINE	200 mV / 23 kΩ
Terminals		
Analogue Input Terminal	LINE x 2 PHONO (MM) x1	
Digital Input Terminal	Optical digital x2 Coaxial digital x1 USB-A x1 USB-B x1	
Analogue Output Terminal	PRE OUT x1	
Digital Output Terminal	HDMI ARC	
Headphone Output	Yes, Stereo Ø6.3 mm	

USB-A	Standard	USB 2.0 High-speed USB Mass Storage class	
	iPod/iPhone/iPad	No	
	Support Codec	WAV	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		FLAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		DSD	Yes (2.8 MHz, 5.6 MHz, 11.2 MHz)
		AIFF	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		ALAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
AAC	Yes (32, 44.1, 48, 88.2, 96 kHz/16-320kbps)		
MP3	Yes (32, 44.1, 48 kHz / 16-320 kbps)		
PC(USB-B)	Standard	USB 2.0 High-speed USB Audio Class 2.0, Asynchronous mode	
	Support Codec	LPCM DSD	
	DSD control mode	ASIO Native mode, DoP mode	
Connectivity			
MQA Decoder		Yes	
LAN (DMR)	Support Codec	WAV	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		FLAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		DSD	Yes (2.8 MHz, 5.6 MHz, 11.2 MHz)
		AIFF	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)
		ALAC	Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit)
		AAC	Yes (32, 44.1, 48, 88.2, 96 kHz/16-320kbps)
		MP3	Yes (32, 44.1, 48 kHz / 16-320 kbps)
Ethernet Interface		LAN (100 Base-TX / 10 Base-T)	
Wi-Fi		IEEE 802.11a/b/g/n/ac/ax 2.4 GHz band / 5 GHz band	
Chromecast Built-In™		Yes	
AirPlay 2		Yes	
Bluetooth® (Support codec)		Yes (AAC, SBC)	
Tuner		DAB/DAB+/FM	
General			
Power Supply		AC 220 V - 240 V, 50/60 Hz	
Power Consumption		63 W	
Dimensions (W x H x D)		430 x 98 x 368 mm	
Weight		Approx. 6,6 kg	
Color		Black	
Accessories		AC Cord, DAB Indoor Antenna, Remote Control, Batteries for Remote Control, Owner's Manual	

